



100% Water Based High Quality Colorable Primer for Wooden Materials

AquaLack®
Color

Contains 85% of pure Nano Acryl WP

Ready to be applied - Any kind of dilution will void the warranty

AquaLack Color is a high quality primer for wooden surfaces. It gives color to the wood and covers totally its original aspect.

It's 100% water based, made from our green 100% acrylic, nano-pollution free nano-resin Nano Acryl HT.

For this reason it does not absorb UV rays as well as Infrared (heat), so it reduces drastically the effects of temperature fluctuation of the protected material.

It does not contain any contaminant component, is APE / APEO free, as well as heavy metals free (lead, cadmium, etc.) and is Low VOC.

It does not smell, it can be applied in interiors without the necessity to evacuate the area.

AquaLack Color is an ecological coating, environmental friendly and absolutely non toxic.

AquaLack Color can be applied on almost kind of wooden materials, giving a final appealing appearance.

It's sandable, to prepare the surface to receive the final lacquer AquaLack Finish.

It is not a finishing lacquer, so after its application it is mandatory to terminate the surface with the application of the final coating AquaLack Finish.

AquaLack Color resists :

Extreme Weather – Salinity and Humidity of Marine Environment
Pollution - Animal Waste - Bird Drops - Permanent Puddles - Inorganic acids

All Nasacoat Coatings are 100% Acrylic - 100% Water Based
Non Toxic - 100% Ecological = Environmental Friendly and Sustainable
as well as

100% Free of cheap monomers : Styrene, Vinyl and VEOVA
100% free of poisoning : Ammonia, Lead, Heavy Metals, Organic Vapors Emission = 0 VOC

Sustainable Materials for a Better and Healthy Future



100% Water Based High Quality Colorable Primer for Wooden Materials

AquaLack®
 Color

Contains 85% of pure Nano Acryl WP

Ready to be applied - Any kind of dilution will void the warranty

Technical Characteristics

Yield per Liter (m ²)	4.0 - 6.0	Flexibility	180°
Content of Nano Acryl HT	85%	Adhesion Strength	> 8.7 MPa
VOC	< 20 g / L - Low VOC	Adhesion Strength x m ²	> 887 Tons
Density	1.5 – 1.6 g / ml	Temperature Resistance	- 25° / + 110°
Solids	60% - 64%	Touch Dry	20 mins.
Viscosity	4,200 - 5,200 cps	Total Drying	40 mins.
pH	8.0 - 9.5	Total Curing time	36 hours
Maximum Storing Time	12 months	Warranty	3 years
Maximum Storage Temperature	35°		

AquaLack Color can be easily applied with common brushes or air sprayers. It does not need any dilution, it's ready to apply.

AquaLack Color is normally applied with 2 or 3 coats, depending of the nature of the substrate material and of the final aspect we want to obtain.

See the Application Manual at : www.nasacoat.com/en/application_manual.pdf

Exclusive Distributor in Mexico :

Nasacoat de México SA de CV Av. López Mateos # 2077 - Plaza del Ángel - Local 9 - Nivel 1,
 Jardines de Plaza del Sol - 44510 Guadalajara, Jalisco - Mexico

Phone : +52 33 3696 10 51 email : team@nasacoat.com www.nasacoat.com