



Almost Invisible Protector Coating for Wooden Walls, Floors and Objects in General

WoodProtector

Contains 50% of pure Nano Acryl EP

Ready to be applied - Any kind of dilution will void the warranty

Warranty	5 years
Yield per Liter	3.0 – 8.0 m ²
Adhesion Strength	more than 800 tons x m ²
Contact Temperature	-25° C / +110° C

Wood Protector can be applied on almost any kind of materials, giving a final appealing appearance. When properly maintained, can last for more than 5 years.

It's washable with common household detergents and chlorine and is Anti-fungi, Anti-algae, Anti-fouling and Auto-cleaning (Hydrophobic, Water repellent, Lotus Effect).

Thanks to its hydrophobic nature, Wood Protector does not permit penetration of water or moisture into any construction materials. However, the layer of Wood Protector is capable to respire.

Wood Protector comes in 2 different versions :

1. Matte (almost invisible)
2. Brilliant

Wood Protector is an almost invisible protective coating for wooden walls, floors and objects in general, for interiors and exteriors.

It protects against UV rays, rain, environmental pollution, animal waste, including bird droppings, sea salinity, etc.

It's made from our green 100% acrylic, nano-pollution free nano-resin Nano Acryl EP.

It does not smell, it can be applied in interiors without the necessity to evacuate the area.

Wood Protector resists :

Extreme Weather – Salinity and Humidity of Marine Environment
 Pollution - Animal Waste - Bird Drops - Permanent Puddles - Inorganic acids

All Nasacoat Coatings are 100% Acrylic - 100% Water Based
 Non Toxic - 100% Ecological = Environmental Friendly and Sustainable
 as well as

100% Free of cheap monomers : Styrene, Vinyl and VEOVA
 100% free of poisoning : Ammonia, Lead, Heavy Metals, Organic Vapors Emission = 0 VOC

Sustainable Materials for a Better and Healthy Future



Almost Invisible Protector Coating for Wooden Walls, Floors and Objects in General

WoodProtector

Contains 50% of pure Nano Acryl EP

Ready to be applied - Any kind of dilution will void the warranty

Technical Characteristics

Yield per Liter (m ²)	3.0 – 8.0	Flexibility	180°
Content of Nano Acryl EP	50%	Adhesion Strength	> 7.9 MPa
VOC	< 5 g / L - 0 VOC	Adhesion Strength x m ²	> 800 Tons
Density	1.10 g / ml	Temperature Resistance	- 25° / + 110°
Solids	21%	Touch Dry	1 hour.
Viscosity	150 - 200 cps	Total Drying	2 hours
pH	8.0 - 9.5	Total Curing time	36 hours
Maximum Storing Time	12 months	Warranty	5 years
Maximum Storage Temperature	35°	Available in containers of 1, 4, 19 and 200 Liters	

Wood Protector can be easily applied with common brushes, rollers or, as best solution, with airless machine. It does not need any dilution, it's ready to apply.

Wood Protector is normally applied with 1 coat only, without any primer. On very porous wooden materials, Wood Protector may require more than one coat.

See the Application Manual at : www.nasacoat.com/en/application_manual.pdf

Exclusive Distributor in Mexico :

Nasacoat de México SA de CV Av. López Mateos # 2077 - Plaza del Ángel - Local 9 - Nivel 1,
 Jardines de Plaza del Sol - 44510 Guadalajara, Jalisco - Mexico

Phone : +52 33 3696 10 51 email : team@nasacoat.com www.nasacoat.com